



Material #111: White Semi-Gloss Paper Label designed for Water-Based Inkjet Printers.

Facestock

Description: Economical semi-gloss white paper label uniquely receptive to inkjet label printing designed to provide excellent print quality and very good moisture and smudge resistance.

Thickness:

4.0 Mil \pm 10%

Adhesive:

Description: Permanent adhesive with high initial tack designed for good adhesion to corrugated cardboard and plastics. Meets the requirements of FDA 21 CFR 175.105 for indirect food contact.

Type: Emulsion Acrylic

Liner:

Description: White kraft paper liner with good lay-flat characteristics and printability.

Caliper: 2.7 Mil \pm 10%

Total Construction Caliper: 7.5 Mil \pm 10%

Minimum Application Temperature: 38° F (3° C)

Service Temperature Range: -65° F to +200° F (-54° C to 93° C)

Storage Considerations:

QuickLabel warrants that this label/tag product retains its performance properties for one year from the date of purchase if properly stored at room conditions between 64-84°F (18-29°C) and 50% relative humidity. Do not store in direct sunlight. Do not remove protective packaging until product is to be used.

Recommended Applications: Material# 111 is an economical choice and ideal for use in inkjet label printing applications where a semi-gloss finish and full-color images and barcodes are desired, as in food, beverage, pharmaceutical, and cosmetics packaging. This material complies with US Food and Drug Administration standards regulating indirect food contact.

Updated on: 11/19/2017